

Always. Reliable. Tight.

hauff
technik®



Individual press seals for cables

The press seals for special requirements.

Product overview

Individual press seal for cable HRD

MPA-tested
tightness



closed design:
for newly installed cables
article code: HRD (D)-2(F)-z/(d)



split design:
for already installed cables
article code: HRD (D)-1G(F)-z/(d)



split, eccentric design:
for already installed cables which are
not positioned centricly
article code: HRD (D)-2G(F)-z/(d)-ex-m



blind insert:
for pressure-tight sealing of reserve openings
article code: HRD (D)-2(F)-0

Features and technical data:

- absolutely gas- and watertight
- sealing width 30 mm:
application: standing seepage water, pressing water
waterproof concrete stress class 1
- sealing width 60 mm:
application: high stress (chemical, thermal), difficult installation conditions
- pressure plates made of V2A (AISI 304L) or V4A (AISI 316L) stainless steel,
washers and nuts made of V4A (AISI 316L)
- can be manufactured exactly to your requirements
- easy to install
- available with overlapping flange (F) as an option



The press seals for special requirements.

Our individual press seals for cables provide you with all the options for the reliable sealing of wall penetrations for one or more cables. The press seals can be installed from one or both sides in a wall sleeve or concrete core drill hole and provide an absolutely gas- and watertight seal. We will deliver any version for diameters > 50 mm quickly and at a reasonable price. All our pressure plates are made of stainless steel (AISI 304L or AISI 316L).

Individual press seals for cables

Article code

HRD (D)-2G(F)-z/(d)-ex-m	
HRD	System designation
(D)	measured inner diameter of conduit/core drilling
1	sealing width 30 mm
2	sealing width 60 mm
G	split design
F	covering flange
z	number of entries
(d)	measured outer diameter of the cable
ex-m	eccentric (shortest distance at least 20 mm)



On-site examples

TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDING
DINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIA
ABLE.ALWAYS.TIGHT.CABLE.PIPE BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE
BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.P
ABLE.PIPE BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY
TRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALV
LWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.B
BUILDINGENTRY ALWAYS.RELIABLE ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.P
AYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIG
LE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.P
LE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.AL
ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS
S.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILD
DINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.FITTA
CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENT
NTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.FITTA

ALWAYS HAUFF